

# Tender specification TCS50

| OZ | Item description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Quantity<br>Qty | Individual amount<br>in EUR | Total amount<br>in EUR |
|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------------------|------------------------|
|    | <p><b>Frameless in aluminium<br/>for inswing doors</b></p> <p>Number of panels:<br/>Basic dimension:<br/>Clearance dimension:<br/>Wall thickness:</p> <p>Frameless in raw untreated aluminium alloy EN EW-6060,<br/>for inswing doors without visible edge on the wall side,<br/>including support for the mesh to snap-in, corner<br/>connectors and bottom spreader bars to guarantee an<br/>easy assembly, moveable wall fixing brackets for a stable<br/>connection between frame and wall, mesh to snap-in to<br/>avoid wall crackings, incl. milling for striking plates and<br/>hinges according specifications.<br/>Door leaf thickness: 49/50 mm<br/>Installation point:<br/>Door no:</p> | ..... pcs.      | .....                       | .....                  |

**Frameless  
for inswing doors**

AGS-systems srl, TCS50 profiles,  
Item no. 10650  
or similar