



Concealed profiles for shadow gaps

S20 for solid and dry construction

Drywall construction



Solid construction

**Description**

The S20 aluminium profile is used to create wall flush shadow gaps. With its clear lines and a seamless transition between wall and floor it enhances the visual effect of the room and meets modern design standards. Due to their special design, there is no direct contact between the floor and the wall, meaning that no impact noise is transmitted. The profiles are useable in many different ways and can be also installed on stairs.

Material



The shadow gaps profiles consist of a black anodized aluminium alloy EN EW-6060 (Al-MgSi) with a possible toleration according to UNI EN 755-9. This alloy offers good strength value, is corrosion-resistant and is particularly suitable as a construction material for high surface requirements.

Cement and its derivatives produce, in wet conditions, alkaline substances which could possibly lead to corrosion.

Aluminium is not resistant to all chemical compounds, therefore contact with hydrogen chloride (HCl) and phosphoric acid (H₃PO₄) should be avoided.

Products for cleaning stones, ceramics etc. can also damage the surface.

However, as the flush-mounted profile is not directly visible, this has no influence on the quality in the installed condition.

Moisture or salt water can discolour the surface of the profile.

Installation



The profiles enable accurate and quick installation, ensuring perfect lines. The installation can be carried out with or without subfloor and is carried out before the plastering work.

With regard to installation in apartments or houses with proof of energy efficiency, it is recommended to obtain detailed information.

Please read the assembly instructions carefully before starting the assembly work. For a professional installation only the recommended materials from AGS-systems must be used, otherwise every liability expires.

Assembly and installing video:



solid construction



dry construction


Shadow gaps



No baseboards are attached to the S20 flush-mounted profiles, as these are shadow gap profiles.

Profiles

The aluminium profiles are provided with a protective foil and are supplied with a length of 2000 mm.



S20 profile		
<u>Solid construction</u>		
Description	Item number	Height
S20	10020	20 mm
<u>Drywall construction</u>		
Description	Item number	Height
S20	10020	20 mm

We guarantee for a high quality of our products. Our processing guidelines are based on tests and practical experiences; they are only indication without assurance of properties, we have no influence on condition of construction sites and the realizations of the works. Country specific regulations, which consist on regional standards, building regulations, processing and industrial guidelines, can guide to specific processing recommendations.